



CONDENSED SPEC SHEET*

Grade Name: INDOBARR 1PE

Indobarr is a fully coated Folding Box Board (FBB) with a thin extrusion coating of LDPE. It is designed for food service & deep freeze packaging.

SUBSTANCE (GSM)	CALIPER (µM)	BENDING RESISTANCE(L&W) mN		
Tonni T 410	Tonni T 411	Tappi T 556		
Tappi T 410	Tappi T 411	MD	CD	GM
215	330	152	77	108
235	362	212	109	152
255	394	271	140	195
285	447	375	181	261
300	472	411	215	297
305	480	441	234	321
325	512	560	294	406
345	548	677	335	476
365	581	766	363	527
TOL: ± 5%	± 5%			±15%

		ts

Indobarr 2PE - Poly Coated on both sides

CONSTRUCTION



Note:

- 1. All Properties are according to ITC PSPD Measurements
- 2. Test Climate 23°C \pm 1 & 50% \pm 2 RH
- 3. Tolerances are based upon 95% Confidence limits of single mill measurements of conditioned random samples
- 4. All parameters are measured as per relevant Tappi standards

PARAMETER	UNITS	VALUE
POLY SUBSTANCE (AVG) BACK	GSM	15 ± 1.5
POLY ADHESION STRENGTH (AVG)	Points	3 MIN
SURFACE TENSION BACK	Dynes/cm	38 MIN
ROUGHNESS - BENDTSEN (AVG)	ml/min	
TOP		50(100 MAX)
воттом		300(500 MAX)
MOISTURE CONTENT	%	6.0±1.0
SURFACE STRENGTH		
IGT PICK (MED.VISCOSITY)		
TOP	m/sec	0.7 MIN
COBB (180 sec) FILLER LAYER	GSM	100 MAX

CERTIFICATIONS & COMPLIANCES		
Manufacturing	ISO 9001, ISO 14001, ISO 45001, BRC Global Standard	
Environmental & Safety	FSC®CoC, SMETA 4 Pillar	
Regulatory	REACH, ROHS	
Food Contact	BfR Recommendation XXXVI US FDA CFR 21, §176.170 US FDA CFR 21, §176.180	





F&B





PHARMA



FMCG

LIQUOR

^{*}ITC PSPD is a dynamic organization, constantly evolving in response to customer needs. The specifications are therefore subject to change. For latest spec sheet, contact marketing.itcpspd@itc.in